

JIS 3装槽型キャリヤローラ TC型

ベルト幅	型式	a=20°		a=30°		a=35°		a=45°		D	I	m	A	H1	H2	n	B	t	a × b	重量 (Kg)			
		H3	L	H3	L	H3	L	H3	L											a=20°	a=30°	a=35°	a=45°
		400	ITC-300-40	223	461	246	423	256	401											276	389	89.1	145
450	ITC-300-45	230	518	256	477	267	453	290	437	89.1	165	690	740	125	170	140	190	6	15 × 25	12	12	12	12
500	ITC-300-50	235	562	263	518	276	493	301	474	89.1	180	740	790	125	170	140	190	6	15 × 25	12	13	13	13
600	ITC-300-60	260	648	293	600	308	572	337	546	89.1	210	840	890	140	185	150	200	6	15 × 25	14	14	14	15
750	ITC-300-75	301	798	344	756	363	721	398	678	114.3	265	1040	1090	150	207	160	210	6	15 × 25	22	22	23	24
900	ITC-300-90	318	942	369	893	391	853	434	799	114.3	315	1190	1240	150	207	160	210	6	15 × 25	25	26	27	27
1050	ITC-300-105	381	1115	441	1053	467	1005	516	934	139.8	370	1340	1390	180	250	180	230	9	15 × 25	36	37	38	39
1200	ITC-300-120	398	1259	466	1190	495	1137	551	1055	139.8	420	1490	1540	180	250	180	230	9	15 × 25	43	44	46	47
1400	ITC-300-140	508	1490	589	1414	625	1352	690	1247	165.2	500	1730	1795	250	333	280	340	9	19 × 32	72	74	77	78
1600	ITC-300-160	535	1720	629	1633	670	1563	747	1440	165.2	580	1930	1995	250	333	280	340	9	19 × 32	95	97	98	100
1800	ITC-300-180	589	1922	694	1824	741	1747	833	1633	165.2	650	2220	2285	280	363	330	390	9	19 × 32	108	111	112	114
2000	ITC-300-200	617	2152	734	2042	786	1959	890	1826	165.2	730	2420	2485	280	363	330	390	9	19 × 32	131	134	135	137

インパクトキャリヤローラ ITC-M型

ベルト幅	型式	a=20°		a=30°		a=35°		a=45°		D	I	m	A	H1	H2	n	B	t	a × b	重量 (Kg)			
		H3	L	H3	L	H3	L	H3	L											a=20°	a=30°	a=35°	a=45°
		400	IITC-300-40-M	228	457	250	417	260	394											280	381	100	145
450	IITC-300-45-M	235	515	260	472	272	447	294	430	100	165	690	740	125	175	140	190	6	15 × 25	13	13	14	14
500	IITC-300-50-M	240	558	268	513	280	487	305	466	100	180	740	790	125	175	140	190	6	15 × 25	13	14	14	14
600	IITC-300-60-M	265	644	298	595	312	566	341	538	100	210	840	890	140	190	150	200	6	15 × 25	15	15	15	16
750	IITC-300-75-M	301	797	344	756	363	721	399	677	115	265	1040	1090	150	208	160	210	6	15 × 25	22	22	23	23
900	IITC-300-90-M	318	941	369	893	392	852	434	798	115	315	1190	1240	150	208	160	210	6	15 × 25	25	26	27	27
1050	IITC-300-105-M	381	1114	441	1053	467	1005	516	934	140	370	1340	1390	180	250	180	230	9	15 × 25	37	38	40	40
1200	IITC-300-120-M	398	1258	466	1189	495	1137	551	1054	140	420	1490	1540	180	250	180	230	9	15 × 25	45	45	47	49
1400	IITC-300-140-M	508	1490	589	1414	625	1351	691	1246	166	500	1730	1795	250	333	280	340	9	19 × 32	77	78	81	82
1600	IITC-300-160-M	536	1720	629	1632	671	1562	747	1439	166	580	1930	1995	250	333	280	340	9	19 × 32	95	98	91	100
1800	IITC-300-180-M	590	1922	694	1823	741	1747	834	1633	166	650	2220	2285	280	363	330	390	9	19 × 32	113	115	116	118
2000	IITC-300-200-M	617	2152	734	2042	787	1958	890	1826	166	730	2420	2485	280	363	330	390	9	19 × 32	136	139	140	142

自動調芯キャリヤローラ ATC型

ベルト幅	型式	a=20°		a=30°		a=35°		a=45°		D1	I1	D2	I2	m	A	H1	h	K	n	B	t	a × b	重量 (Kg)			
		H3	L	H3	L	H3	L	H3	L														a=20°	a=30°	a=35°	a=45°
		400	IATC-300-40	223	461	246	423	256	401														276	389	89.1	145
450	IATC-300-45	230	518	256	477	267	453	290	437	89.1	165	76.3	120	690	740	170	68	200	140	190	4.5	15 × 25	21	21	22	22
500	IATC-300-50	235	562	263	518	276	493	301	474	89.1	180	76.3	120	740	790	170	68	200	140	190	4.5	15 × 25	22	22	22	23
600	IATC-300-60	260	648	293	600	308	572	337	546	89.1	210	76.3	120	840	890	185	53	200	150	200	4.5	15 × 25	24	24	24	24
750	IATC-300-75	301	798	344	756	363	721	398	678	114.3	265	76.3	120	1040	1090	207	60	200	160	210	6	15 × 25	35	35	35	35
900	IATC-300-90	318	942	369	893	391	853	434	799	114.3	315	76.3	120	1190	1240	207	67	200	160	210	6	15 × 25	39	39	40	40
1050	IATC-300-105	381	1115	441	1053	467	1005	516	934	139.8	370	89.1	150	1340	1390	250	56	240	180	230	9	15 × 25	58	58	59	59
1200	IATC-300-120	398	1259	466	1190	495	1137	551	1055	139.8	420	89.1	150	1490	1540	250	70	240	180	230	9	15 × 25	67	68	68	69
1400	IATC-300-140	508	1490	589	1414	625	1352	690	1247	165.2	500	114.3	180	1730	1795	333	52	240	280	340	9	19 × 32	134	138	139	141
1600	IATC-300-160	535	1720	629	1633	670	1563	747	1440	165.2	580	114.3	180	1930	1990	333	73	240	280	340	9	19 × 32	158	163	164	167
1800	IATC-300-180	589	1922	694	1824	741	1747	833	1633	165.2	650	114.3	180	2220	2280	363	43	240	330	390	9	19 × 32	188	194	196	199
2000	IATC-300-200	617	2152	734	2042	786	1959	890	1826	165.2	730	114.3	180	2420	2480	363	43	240	330	390	9	19 × 32	217	225	227	230